

DEPENDENT RESURVEY OF PORTIONS OF MINERAL SURVEY NO. 55,
T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Continue measurement on line 5-1, Mineral Survey No. 55, Keystone claim.
1.00	Powerline, bears S. 15° E. and N. 15° W.
1.44	Nevada State Route 342, asphalt surface, 35 lks. wide, bears S. 15° E. and N. 15° W.
1.901	Intersect line 4-5, Lot No. 43, Block 8, Range D, Gold Hill Townsite, at a point from which the point for Angle Point No. 4, identical with Angle Point No. 1, Lot No. 43 1/2, Block 8, Range D, Gold Hill Townsite, hereinafter described, bears S. 21°51'20" E., 0.822 chs. dist.
3.030	Cor. No. 1, Mineral Survey No. 55, Keystone claim.
	DEPENDENT RESURVEY OF A PORTION OF MINERAL SURVEY NO. 65, T. 16 N., R. 21 E., MOUNT DIABLO MERIDIAN, NEVADA Reestablishment of a Portion of the Survey Executed by U.S. Deputy Mineral Surveyor H. Hochholzer in 1873 Alta claim on the Woodville lode From Cor. No. 1, Mineral Survey No. 65, Alta claim, on line 3-4, Mineral Survey No. 53, Woodville claim, monumented with a basalt stone, 22x8x7 ins., firmly set, projecting 4 ins. above the ground, mkd. x on top face and P1 on NE. face, with a mound of stone 2 1/2 ft. base, 1 1/2 ft. high, SW. of cor., and a steel fence post set alongside. At the corner point Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd. Bury the mkd. stone in the mound of stone, alongside the stainless steel post. Thence N. 9°07'10" W., on line 1-2, Mineral Survey No. 65, Alta claim.
1.095	Cor. No. 6, Mineral Survey No. 100, Memphis claim, hereinafter described.