

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 24 S., R. 57 E., MOUNT DIABLO MERIDIAN, NEVADA

CHAINS	Reestablishment of the Survey Executed by U.S. Deputy Surveyors J.M. Brunt and W.H. Proctor in 1881
	From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., hereinbefore described. N. 9°55'00" E., bet. secs. 35 and 36.
1.40	Enter wash, drains WSW.
3.80	Trail road, 10 lks. wide, bears irregularly E. and W.
5.60	Exit wash.
41.086	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, over a plastic-encased magnet, and in a collar of stone, with brass cap mkd. T24S R57E 1/4 S35 S36 2017
68.00	Spur, slopes SE.
76.90	Gulch, 15 lks. wide, drains SE.
82.172	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, over a plastic-encased magnet, and in a mound of stone, 4 ft. base, to top, with brass cap mkd. T24S R57E S26 S25 S35 S36 2017 From this point, Cor. No. 3, Mineral Survey No. 2002, Old Timer lode, hereinafter described, bears N. 24°48'10" E., 36.516 chs. dist. From this same point, Cor. No. 3, Mineral Survey No. 4366, Eureka lode, hereinafter described, bears N. 46°46'20" E., 39.282 chs. dist.